

Chemical Safety Data Sheet MSDS / SDS

1,3-Bis(aminomethyl)benzene

Revision Date:2025-07-19 Revision Number:1

SECTION 1: Identification of the substance/mixture and of the company/undertaking**Product identifier**

Product name : 1,3-Bis(aminomethyl)benzene
CBnumber : CB6307422
CAS : 1477-55-0
EINECS Number : 216-032-5
Synonyms : MXDA,m-Xylylenediamine

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : For R&D use only. Not for medicinal, household or other use.
Uses advised against : none

Company Identification

Company : Chemicalbook
Address : Building 1, Huihuang International, Shangdi 10th Street, Haidian District, Beijing
Telephone : 010-86108875

SECTION 2: Hazards identification**GHS Label elements, including precautionary statements**

Symbol(GHS)



Signal word

Danger

Precautionary statements

P501 Dispose of contents/container to.....

P405 Store locked up.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P310 Immediately call a POISON CENTER or doctor/physician.

P307+P311 IF exposed: call a POISON CENTER or doctor/physician.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continuerinsing.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P273 Avoid release to the environment.

P272 Contaminated work clothing should not be allowed out of the workplace.

P271 Use only outdoors or in a well-ventilated area.

P270 Do not eat, drink or smoke when using this product.

P264 Wash skin thoroughly after handling.

P264 Wash hands thoroughly after handling.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

Hazard statements

H412 Harmful to aquatic life with long lasting effects

H371 May cause damage to organs

H370 Causes damage to organs

H331 Toxic if inhaled

H317 May cause an allergic skin reaction

H314 Causes severe skin burns and eye damage

SECTION 3: Composition/information on ingredients

Substance

Product name	: 1,3-Bis(aminomethyl)benzene
Synonyms	: MXDA,m-Xylylenediamine
CAS	: 1477-55-0
EC number	: 216-032-5
MF	: C ₈ H ₁₂ N ₂
MW	: 136.19

SECTION 4: First aid measures

Description of first aid measures

General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

In case of eye contact

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: make victim drink water (two glasses at most), avoid vomiting (risk of perforation). Call a physician immediately. Do not attempt to neutralise.

Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media

Water Foam Carbon dioxide (CO₂) Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

Special hazards arising from the substance or mixture

Carbon oxides Nitrogen oxides (NO_x) Combustible.

Vapors are heavier than air and may spread along floors. Forms explosive mixtures with air on intense heating.

Development of hazardous combustion gases or vapours possible in the event of fire.


Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

Further information

Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

NFPA 704



■ HEALTH	4	Very short exposure could cause death or major residual injury (e.g. hydrogen cyanide, phosgene, methyl isocyanate, hydrofluoric acid)
■ FIRE	1	Materials that require considerable preheating, under all ambient temperature conditions, before ignition and combustion can occur. Includes some finely divided suspended solids that do not require heating before ignition can occur. Flash point at or above 93.3 °C (200 °F). (e.g. mineral oil , ammonia)
■ REACT	0	Normally stable, even under fire exposure conditions, and is not reactive with water (e.g. helium, N₂)
□ SPEC.		
□ HAZ.		

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

Environmental precautions

Do not let product enter drains.

Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent and neutralising material (e.g. Chemizorb? OH ? , Merck Art. No. 101596). Dispose of properly. Clean up affected area.

Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed.

Storage class

Storage class (TRGS 510): 8A: Combustible, corrosive hazardous materials

Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

control parameter

Hazard composition and occupational exposure limits

Does not contain substances with occupational exposure limits.

Exposure controls

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly fitting safety goggles

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.

Full contact

Material: Chloroprene

Minimum layer thickness: 0,6 mm Break through time: 480 min

Material tested: Camapren? (KCL 722 / Aldrich Z677493, Size M)

Splash contact

Material: Nature latex/chloroprene Minimum layer thickness: 0,6 mm Break through time: 30 min

Material tested: Lapren? (KCL 706 / Aldrich Z677558, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

protective clothing

Respiratory protection

required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Recommended Filter type: Filter type ABEK

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

Control of environmental exposure

Do not let product enter drains.

SECTION 9: Physical and chemical properties

Information on basic physicochemical properties

Appearance	colorless clear, liquid
------------	-------------------------

Odour	amine-like
-------	------------

Odour Threshold	No data available
-----------------	-------------------

pH	12 at 1 g/l at 20 °C
----	----------------------

Melting point/freezing point	Melting point: 14 °C - OECD Test Guideline 102
Initial boiling point and boiling range	265 °C at 993 hPa - lit.
Flash point	113 °C - closed cup
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Upper/lower flammability or explosive limits	No data available
Vapour pressure	0,01 hPa at 25 °C - OECD Test Guideline 104
Vapour density	No data available
Relative density	1,032 g/cm ³ at 25 °C - lit. No data available
Water solubility	100 g/l at 20 °C - OECD Test Guideline 105- miscible in all proportions
Partition coefficient: n-octanol/water	log Pow: ca.0,18 at 25 °C - OECD Test Guideline 107 - Bioaccumulation is not expected.
Autoignition temperature	395 - 405 °C at 1.006,9 - 1.013,1 hPa
Decomposition temperature	No data available
Viscosity	Viscosity, kinematic: 6,78 mm ² /s at 20 °C - OECD Test Guideline 114 Viscosity, dynamic: No data available
Explosive properties	No data available
Oxidizing properties	No data available

Other safety information

No data available

SECTION 10: Stability and reactivity

Reactivity

Forms explosive mixtures with air on intense heating.

A range from approx. 15 Kelvin below the flash point is to be rated as critical.

Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

Possibility of hazardous reactions

No data available

Conditions to avoid

Strong heating.

Incompatible materials

acids, Acid chlorides, Acid anhydrides, Oxidizing agents, Chloroformates

Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - 930 mg/kg

Remarks: (RTECS)

Acute toxicity estimate Inhalation - 4 h - 11 mg/l (Expert judgment)

Acute toxicity estimate Inhalation - 4 h - 11 mg/l (Expert judgment)

LD50 Dermal - Rat - male and female - > 3.100 mg/kg Remarks: (ECHA)

Skin corrosion/irritation

Skin - Rat

Result: Causes burns. - 4 h

(Directive 67/548/EEC, Annex V, B.4.)

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Local lymph node assay (LLNA) - Mouse

Result: positive

(OECD Test Guideline 429)

Germ cell mutagenicity

Test Type: Ames test

Test system: Escherichia coli/Salmonella typhimurium Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 471

Result: negative

Test Type: Chromosome aberration test in vitro Test system: Chinese hamster ovary cells Metabolic activation: without metabolic activation

Method: OECD Test Guideline 473

Result: negative

Test Type: In vitro mammalian cell gene mutation test Test system: mouse lymphoma cells

Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 476

Result: negative

Test Type: In vivo micronucleus test Species: Mouse

Cell type: Bone marrow

Method: OECD Test Guideline 474 Result: negative

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Corrosive to the respiratory tract.

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

SECTION 12: Ecological information

Toxicity

Toxicity to fish

semi-static test LC50 - *Oryzias latipes* (Orange-red killifish) - 87,6 mg/l - 96 h
(OECD Test Guideline 203)

Toxicity to daphnia and other aquatic invertebrates

static test EC50 - *Daphnia magna* (Water flea) - 15,2 mg/l - 48 h (OECD Test Guideline 202)

Toxicity to algae

static test ErC50 - *Pseudokirchneriella subcapitata* (algae) - 33,3 mg/l - 72 h
(OECD Test Guideline 201)

Toxicity to bacteria

static test EC50 - activated sludge - > 1.000 mg/l - 0,5 h (OECD Test Guideline 209)

Persistence and degradability

Biodegradability aerobic - Exposure time 28 d

Result: 49 % - Not readily biodegradable. (OECD Test Guideline 301B)

Bioaccumulative potential

No data available

Mobility in soil

No data available

Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Toxics Screening Level

The ITSL for 1,3-Bis(aminomethyl)benzene is 1 µg/m³ based on a 1 hour averaging time.

Other adverse effects

No data available

SECTION 13: Disposal considerations

Waste treatment methods

Product

See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

Incompatibilities

Combustible; vapors may form explosive mixture with air. Incompatible with oxidizers (chlorates, nitrates, peroxides, permanganates,

perchlorates, chlorine, bromine, fluorine, etc.); contact may cause fires or explosions. Keep away from alkaline materials, strong bases, strong acids, oxoacids, and epoxides.

SECTION 14: Transport information

UN number

ADR/RID: 2735 IMDG: 2735 IATA: 2735

UN proper shipping name

ADR/RID: POLYAMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine)) IMDG: POLYAMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine)) IATA: Polyamines, liquid, corrosive, n.o.s. (m-phenylenebis(methylamine))

Transport hazard class(es)

ADR/RID: 8 IMDG: 8 IATA: 8

Packaging group

ADR/RID: II IMDG: II IATA: II

Environmental hazards

ADR/RID: no IMDG Marine pollutant: no IATA: no

Special precautions for user

No data available

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations on the Safety Management of Hazardous Chemicals

China Catalog of Hazardous chemicals 2015:Not Listed. website: <https://www.mem.gov.cn/>

Measures for Environmental Management of New Chemical Substances

United States Toxic Substances Control Act (TSCA) Inventory:Listed. website: <https://www.epa.gov/>

New Zealand Inventory of Chemicals (NZIoC):Listed. website: <https://www.epa.govt.nz/>

European Inventory of Existing Commercial Chemical Substances (EINECS):Listed. website: <https://echa.europa.eu/>

Philippines Inventory of Chemicals and Chemical Substances (PICCS):Listed. website: <https://emb.gov.ph/>

EC Inventory:Listed.

Vietnam National Chemical Inventory:Listed. website: <https://chemicaldata.gov.vn/>

Korea Existing Chemicals List (KECL):Listed. website: <http://ncis.nier.go.kr>

Chinese Chemical Inventory of Existing Chemical Substances (China IECSC):Listed. website: <https://www.mee.gov.cn/>

SECTION 16: Other information

Abbreviations and acronyms

CAS: Chemical Abstracts Service

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

RID: Regulation concerning the International Carriage of Dangerous Goods by Rail

IMDG: International Maritime Dangerous Goods

IATA: International Air Transportation Association

TWA: Time Weighted Average

STEL: Short term exposure limit

LC50: Lethal Concentration 50%

LD50: Lethal Dose 50%

EC50: Effective Concentration 50%

References

- 【1】 CAMEO Chemicals, website: <http://cameochemicals.noaa.gov/search/simple>
- 【2】 ChemIDplus, website: <http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp>
- 【3】 ECHA - European Chemicals Agency, website: <https://echa.europa.eu/>
- 【4】 eChemPortal - The Global Portal to Information on Chemical Substances by OECD, website:
http://www.echemportal.org/echemportal/index?pageID=0&request_locale=en
- 【5】 ERG - Emergency Response Guidebook by U.S. Department of Transportation, website: <http://www.phmsa.dot.gov/hazmat/library/erg>
- 【6】 Germany GESTIS-database on hazard substance, website: <http://www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index-2.jsp>
- 【7】 HSDB - Hazardous Substances Data Bank, website: <https://toxnet.nlm.nih.gov/newtoxnet/hsdb.htm>
- 【8】 IARC - International Agency for Research on Cancer, website: <http://www.iarc.fr/>
- 【9】 IPCS - The International Chemical Safety Cards (ICSC), website: <http://www.ilo.org/dyn/icsc/showcard.home>
- 【10】 Sigma-Aldrich, website: <https://www.sigmaaldrich.com/>

Other Information

The symptoms of lung oedema often do not become manifest until a few hours have passed and they are aggravated by physical effort. Rest and medical observation is therefore essential. The occupational exposure limit value should not be exceeded during any part of the working exposure.

Disclaimer:

The information in this MSDS is only applicable to the specified product, unless otherwise specified, it is not applicable to the mixture of this product and other substances. This MSDS only provides information on the safety of the product for those who have received the appropriate professional training for the user of the product. Users of this MSDS must make independent judgments on the applicability of this SDS. The authors of this MSDS will not be held responsible for any harm caused by the use of this MSDS.