

Chemical Safety Data Sheet MSDS / SDS

1,5-HEXADIENE

Revision Date:2025-02-01 Revision Number:1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product name : 1,5-HEXADIENE
CBnumber : CB4391362
CAS : 592-42-7
EINECS Number : 209-754-7
Synonyms : 1,5-hexadiene,hexadiene

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : For R&D use only. Not for medicinal, household or other use.
Uses advised against : none

Company Identification

Company : Chemicalbook
Address : Building 1, Huihuang International, Shangdi 10th Street, Haidian District, Beijing
Telephone : 400-158-6606

SECTION 2: Hazards identification

GHS Label elements, including precautionary statements

Symbol(GHS)



Signal word

Danger

Precautionary statements

P501 Dispose of contents/container to.....

P405 Store locked up.

P403+P235 Store in a well-ventilated place. Keep cool.

P391 Collect spillage. Hazardous to the aquatic environment

P370+P378 In case of fire: Use ... for extinction.

P331 Do NOT induce vomiting.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continuerinsing.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P273 Avoid release to the environment.

P264 Wash skin thoroughly after handling.

P264 Wash hands thoroughly after handling.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P240 Ground/bond container and receiving equipment.

P233 Keep container tightly closed.

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

Hazard statements

H411 Toxic to aquatic life with long lasting effects

H335 May cause respiratory irritation

H319 Causes serious eye irritation

H315 Causes skin irritation

H304 May be fatal if swallowed and enters airways

H225 Highly Flammable liquid and vapour

SECTION 3: Composition/information on ingredients

Substance

Product name	: 1,5-HEXADIENE
Synonyms	: 1,5-hexadiene,hexadiene
CAS	: 592-42-7
EC number	: 209-754-7
MF	: C ₆ H ₁₀
MW	: 82.14

SECTION 4: First aid measures

Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media

Dry powder Dry sand

Unsuitable extinguishing media

Do NOT use water jet.

Special hazards arising from the substance or mixture

Carbon oxides Combustible.


Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

Further information

Use water spray to cool unopened containers.

NFPA 704



☒ HEALTH 2 Intense or continued but not chronic exposure could cause temporary incapacitation or possible residual injury (e.g. [diethyl ether](#), ammonium phosphate, iodine)

☒ FIRE 3 Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions . Liquids having a flash point below 22.8 °C (73 °F) and having a boiling point at or above 37.8 °C (100 °F) or having a flash point between 22.8 and 37.8 °C (73 and 100 °F). (e.g. gasoline, [acetone](#))

☒ REACT 2 Undergoes violent chemical change at elevated temperatures and pressures, reacts violently with water, or may form explosive mixtures with water (e.g. white phosphorus, [potassium](#), [sodium](#))

☐ SPEC.

☐ HAZ.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in cool place.

Recommended storage temperature 2 - 8 °C

Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

control parameter

Hazard composition and occupational exposure limits

Does not contain substances with occupational exposure limits.

Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.

Full contact

Material: Fluorinated rubber Minimum layer thickness: 0,7 mm Break through time: 480 min

Material tested: Vitoject? (KCL 890 / Aldrich Z677698, Size M)

Splash contact Material: Nitrile rubber

Minimum layer thickness: 0,4 mm Break through time: 240 min

Material tested: Camatril? (KCL 730 / Aldrich Z677442, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Impervious clothing, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full- face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

SECTION 9: Physical and chemical properties

Information on basic physicochemical properties

Appearance	liquid
Odour	No data available
Odour Threshold	No data available
pH	No data available
Melting point/freezing point	Melting point/range: -141 °C - lit.
Initial boiling point and boiling range	60 °C - lit.
Flash point	-27 °C - closed cup
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Upper/lower flammability or explosive limits	Upper explosion limit: 6,1 %(V) Lower explosion limit: 1,2 %(V)
Vapour pressure	295 hPa at 25 °C
Vapour density	2,84
Relative density	0,692 g/cm ³ at 25 °C

Water solubility	0,169 g/l at 25 °C
Partition coefficient: n-octanol/water	log Pow: 2,87 - Bioaccumulation is not expected., (Lit.)
Autoignition temperature	No data available
Decomposition temperature	No data available
Viscosity	No data available
Explosive properties	No data available
Oxidizing properties	No data available

Other safety information

Relative vapour density
2,84

SECTION 10: Stability and reactivity

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

No data available

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

No data available

Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides Other decomposition products - No data available
In the event of fire: see section 5

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

LC50 Inhalation - Rat - 4 h - > 360 mg/l Remarks: (RTECS)

Skin corrosion/irritation

Serious eye damage/eye irritation Respiratory or skin sensitisation Germ cell mutagenicity Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

Reproductive toxicity

Specific target organ toxicity - single exposure

May cause respiratory irritation.

Acute oral toxicity - Irritations of mucous membranes in the mouth, pharynx, oesophagus and gastrointestinal tract.

Specific target organ toxicity - repeated exposure Aspiration hazard**Additional Information**

RTECS: MM1997800

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Systemic effects:

Headache, Dizziness, Nausea, respiratory arrest, Unconsciousness Further data:

Other dangerous properties can not be excluded.

Handle in accordance with good industrial hygiene and safety practice.

SECTION 12: Ecological information

Toxicity**Persistence and degradability****Bioaccumulative potential****Mobility in soil****Results of PBT and vPvB assessment**

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Toxics Screening Level

The initial threshold screening level (ITSL) for 1,5-hexadiene is 264 µg/m³ based on an annual averaging time.

Other adverse effects

We have no quantitative data concerning the ecological effects of this product. Further information on ecology

Discharge into the environment must be avoided.

Stability in water

Remarks: The product is insoluble and floats on water.

SECTION 13: Disposal considerations

Waste treatment methods**Product**

Offer surplus and non-recyclable solutions to a licensed disposal company. Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information

UN number

ADR/RID: 2458 IMDG: 2458 IATA: 2458

UN proper shipping name

ADR/RID: HEXADIENES IMDG: HEXADIENES IATA: Hexadiene

Transport hazard class(es)

ADR/RID: 3 IMDG: 3 IATA: 3

Packaging group

ADR/RID: II IMDG: II IATA: II

Environmental hazards

ADR/RID: no IMDG Marine pollutant: no IATA: no

Special precautions for user

No data available

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations on the Safety Management of Hazardous Chemicals

China Catalog of Hazardous chemicals 2015: Listed. website: <https://www.mem.gov.cn/>

Measures for Environmental Management of New Chemical Substances

New Zealand Inventory of Chemicals (NZIoC): Not Listed. website: <https://www.epa.govt.nz/>

Vietnam National Chemical Inventory: Listed. website: <https://chemicaldata.gov.vn/>

United States Toxic Substances Control Act (TSCA) Inventory: Listed. website: <https://www.epa.gov/>

Philippines Inventory of Chemicals and Chemical Substances (PICCS): Listed. website: <https://emb.gov.ph/>

Korea Existing Chemicals List (KECL): Listed. website: <http://ncis.nier.go.kr>

European Inventory of Existing Commercial Chemical Substances (EINECS): Listed. website: <https://echa.europa.eu/>

EC Inventory: Listed.

Chinese Chemical Inventory of Existing Chemical Substances (China IECSC): Listed. website: <https://www.mee.gov.cn/>

SECTION 16: Other information

Abbreviations and acronyms

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

CAS: Chemical Abstracts Service

EC50: Effective Concentration 50%

IATA: International Air Transportation Association

IMDG: International Maritime Dangerous Goods

LC50: Lethal Concentration 50%

LD50: Lethal Dose 50%

RID: Regulation concerning the International Carriage of Dangerous Goods by Rail

STEL: Short term exposure limit

TWA: Time Weighted Average

References

- 【1】 CAMEO Chemicals, website: <http://cameochemicals.noaa.gov/search/simple>
- 【2】 ChemIDplus, website: <http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp>
- 【3】 ECHA - European Chemicals Agency, website: <https://echa.europa.eu/>
- 【4】 eChemPortal - The Global Portal to Information on Chemical Substances by OECD, website:
http://www.echemportal.org/echemportal/index?pageID=0&request_locale=en
- 【5】 ERG - Emergency Response Guidebook by U.S. Department of Transportation, website: <http://www.phmsa.dot.gov/hazmat/library/erg>
- 【6】 Germany GESTIS-database on hazard substance, website: <http://www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index-2.jsp>
- 【7】 HSDB - Hazardous Substances Data Bank, website: <https://toxnet.nlm.nih.gov/newtoxnet/hsdb.htm>
- 【8】 IARC - International Agency for Research on Cancer, website: <http://www.iarc.fr/>
- 【9】 IPCS - The International Chemical Safety Cards (ICSC), website: <http://www.ilo.org/dyn/icsc/showcard.home>
- 【10】 Sigma-Aldrich, website: <https://www.sigmaaldrich.com/>

Disclaimer:

The information in this MSDS is only applicable to the specified product, unless otherwise specified, it is not applicable to the mixture of this product and other substances. This MSDS only provides information on the safety of the product for those who have received the appropriate professional training for the user of the product. Users of this MSDS must make independent judgments on the applicability of this SDS. The authors of this MSDS will not be held responsible for any harm caused by the use of this MSDS.