# Chemical Safety Data Sheet MSDS / SDS

# m-Xylene

Revision Date: 2025-03-01 Revision Number: 1

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **Product identifier**

 Product name
 : m-Xylene

 CBnumber
 : CB4852746

 CAS
 : 108-38-3

 EINECS Number
 : 203-576-3

Synonyms: m-xylene,1,3-dimethylbenzene

## Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : For R&D use only. Not for medicinal, household or other use.

Uses advised against : none

## **Company Identification**

Company : Chemicalbook

Address : Building 1, Huihuang International, Shangdi 10th Street, Haidian District, Beijing

Telephone : 400-158-6606

## SECTION 2: Hazards identification

## GHS Label elements, including precautionary statements

Symbol(GHS)



Signal word Danger

## Precautionary statements

P370+P378 In case of fire: Use ... for extinction.

P331 Do NOT induce vomiting.

P311 Call a POISON CENTER or doctor/physician.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continuerinsing.

P304+P340 IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P273 Avoid release to the environment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

#### **Hazard statements**

H412 Harmful to aquatic life with long lasting effects

H370 Causes damage to organs

H335 May cause respiratory irritation

H332 Harmful if inhaled

H319 Causes serious eye irritation

H315 Causes skin irritation

H312 Harmful in contact with skin

H304 May be fatal if swallowed and enters airways

H226 Flammable liquid and vapour

H225 Highly Flammable liquid and vapour

# SECTION 3: Composition/information on ingredients

#### **Substance**

Product name : m-Xylene

Synonyms: m-xylene,1,3-dimethylbenzene

CAS : 108-38-3
EC number : 203-576-3
MF : C8H10
MW : 106.17

## SECTION 4: First aid measures

## Description of first aid measures

## General advice

Show this material safety data sheet to the doctor in attendance.

## If inhaled

After inhalation: fresh air.

#### In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Consult a physician.

## In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

#### If swallowed

After swallowing: caution if victim vomits. Risk of aspiration! Keep airways free. Pulmonary failure possible after aspiration of vomit. Call a physician immediately.

## Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

No data available

# SECTION 5: Firefighting measures

#### Extinguishing media

#### Suitable extinguishing media

Carbon dioxide (CO2) Foam Dry powder

#### Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

#### Special hazards arising from the substance or mixture

Carbon oxides Combustible.

Vapors are heavier than air and may spread along floors. Forms explosive mixtures with air at elevated temperatures.

Development of hazardous combustion gases or vapours possible in the event of fire.


## Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

#### **Further information**

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

#### **NFPA 704**



Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature

3 conditions . Liquids having a flash point below 22.8 °C (73 °F) and having a boiling point at or above 37.8 °C (100 °F) or FIRE having a flash point between 22.8 and 37.8 °C (73 and 100 °F). (e.g. gasoline, acetone)

REACT 0 Normally stable, even under fire exposure conditions, and is not reactive with water (e.g. helium, N2)

SPEC. 

HAZ.

## SECTION 6: Accidental release measures

## Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition.

Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

## **Environmental precautions**

Do not let product enter drains. Risk of explosion.

## Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquidabsorbent material (e.g.

Chemizorb?). Dispose of properly. Clean up affected area.

## Reference to other sections

For disposal see section 13.

# SECTION 7: Handling and storage

## Precautions for safe handling

## Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

#### Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

## Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

## Conditions for safe storage, including any incompatibilities

## Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

## Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

# SECTION 8: Exposure controls/personal protection

## control parameter

#### Hazard composition and occupational exposure limits

Does not contain substances with occupational exposure limits.

## **Exposure controls**

## Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact Material: Viton?

Minimum layer thickness: 0,7 mm Break through time: 480 min

Material tested: Vitoject? (KCL 890 / Aldrich Z677698, Size M)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact Material: Nitrile rubber

Minimum layer thickness: 0,4 mm Break through time: 30 min

Material tested: Camatril? (KCL 730 / Aldrich Z677442, Size M)

**Body Protection** 

Flame retardant antistatic protective clothing.

Respiratory protection

Recommended Filter type: Filter A (acc. to DIN 3181) for vapours of organic compounds

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

## **Exposure limits**

NIOSH REL: 100 ppm (435 mg/m<sup>3</sup>), STEL 150 ppm (655 mg/m<sup>3</sup>), IDLH 900 ppm; OSHA PEL: TWA 100 ppm; ACGIH TLV: TWA 100 ppm, STEL 150 ppm (adopted).

# SECTION 9: Physical and chemical properties

#### Information on basic physicochemical properties

Appearance	colorless liquid
Odour	No data available
Odour Threshold	0.041ppm
рН	No data available
Melting point/freezing point	Melting point/range: -48 °C - lit.

Initial boiling point and boiling range	138 - 139 °C - lit.
Flash point	27 °C - closed cup
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Upper/lower flammability or explosive	Upper explosion limit: 7 %(V) Lower explosion limit: 1,1 %(V)
limits	
Vapour pressure	13,78 hPa at 29,4 °C
Vapour density	3.7 (vs air)
Relative density	0,868 g/cm3 at 25 °C - lit. 0,86 at 25 °C
Water solubility	146 g/l at 25 °C - partly soluble
Partition coefficient: n-octanol/water	log Pow: 3,2 at 20 °C - Bioaccumulation is not expected.
Autoignition temperature	528,0 °C at 1.013 hPa
Decomposition temperature	No data available
Viscosity	Viscosity, kinematic: No data available Viscosity, dynamic: 0,58 mPa.s at 25 °C
Explosive properties	No data available
Oxidizing properties	No data available
Henry's Law Constant	14.80 at 45.00 °C, 17.26.4 at 50.00 °C, 19.90 at 55.00 °C, 23.01.3 at 60.00 °C, 27.46.3 at 70.00 °C $^{\circ}$
	(static headspace-GC, Park et al., 2004)
•	

## Other safety information

Surface tension 28,47 mN/m at 25 °C

# SECTION 10: Stability and reactivity

# Reactivity

Vapor/air-mixtures are explosive at intense warming.

## **Chemical stability**

The product is chemically stable under standard ambient conditions (room temperature) .

## Possibility of hazardous reactions

Violent reactions possible with: Strong oxidizing agents

conc. sulfuric acid Nitric acid uranium hexafluoride sulfur

## **Conditions to avoid**

Heating.

## Incompatible materials

rubber, various plastics

## Hazardous decomposition products

# **SECTION 11: Toxicological information**

## Information on toxicological effects

#### Acute toxicity

LD50 Oral - Rat - male - 3.523 mg/kg

(EC Directive 92/69/EEC B.1 Acute Toxicity (Oral))

Symptoms: Risk of aspiration upon vomiting., Aspiration may cause pulmonary edema and pneumonitis.

LC50 Inhalation - Rat - male and female - 4 h - 27,12 mg/l (US-EPA)

Symptoms: Inhalation may lead to the formation of oedemas in the respiratory tract. Dermal: Classified according to Regulation (EU)

1272/2008, Annex VI (Table 3.1/3.2)

#### Skin corrosion/irritation

Skin - Rabbit

Result: Moderate skin irritation - 4 h (Regulation (EC) No. 440/2008, Annex, B.4)

Drying-out effect resulting in rough and chapped skin. After long-term exposure to the chemical: Dermatitis

#### Serious eye damage/eye irritation

Eyes - Rabbit

Result: Severe eye irritation - 24 h Remarks: (RTECS)

#### Respiratory or skin sensitization

(OECD Test Guideline 429)

#### Germ cell mutagenicity

Test Type: sister chromatid exchange assay Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation Method: Regulation (EC) No. 440/2008, Annex, B.19 Result: negative

Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 471

Result: negative

Remarks: (National Toxicology Program)

Test Type: Mutagenicity (mammal cell test): chromosome aberration. Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation Method: Mutagenicity (in vitro mammalian cytogenetic test) Result: negative

Test Type: dominant lethal test Species: Mouse

Application Route: Subcutaneous Method: OECD Test Guideline 478 Result: negative

Test Type: Mutagenicity (mammal cell test): micronucleus. Species: Mouse

Cell type: Red blood cells (erythrocytes) Application Route: Intraperitoneal Method: OECD Test Guideline 474 Result: negative

Remarks: (IUCLID)

#### Carcinogenicity

No data available

## Reproductive toxicity

Overexposure may cause reproductive disorder(s) based on tests with laboratory animals.

#### Specific target organ toxicity - single exposure

Inhalation - May cause respiratory irritation.

## Specific target organ toxicity - repeated exposure

No data available

#### **Aspiration hazard**

May be fatal if swallowed and enters airways.

#### **Toxicity**

LD50 orally in rats: 7.71 ml/kg (Smyth)

# **SECTION 12: Ecological information**

## **Toxicity**

#### Toxicity to fish

static test LC50 - Oncorhynchus mykiss (rainbow trout) - 2,60 mg/l

- 96 h

(OECD Test Guideline 203)

#### Toxicity to algae

static test EC50 - Pseudokirchneriella subcapitata - 4,36 mg/l - 73 h (OECD Test Guideline 201)

#### Toxicity to bacteria

Remarks: (ECHA)

(m-xylene)

## Persistence and degradability

Biodegradability aerobic - Exposure time 28 d

Result: 98 % - Readily biodegradable. (OECD Test Guideline 301F)

Chemical Oxygen Demand (COD)

Theoretical oxygen demand

2,62 g/g Remarks: (ECHA)

3,17 g/g Remarks: (ECHA)

Ratio BOD/ThBOD 80 %

Remarks: (ECHA)

## **Bioaccumulative potential**

Bioaccumulation Oncorhynchus mykiss (rainbow trout) - 56 d

at 10 °C - 1,3 mg/l(m-xylene)

Bioconcentration factor (BCF): 7,4 - 18,5

Due to the distribution coefficient n-octanol/water, accumulation in organisms is not expected.

# Mobility in soil

No data available

## Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## **Toxics Screening Level**

The Initial Threshold Screening Level (ITSL) for o-xylene (CAS # 95-47-6), p-xylene (CAS # 106-42-3), m-xylene (CAS # 108-38-3), and xylenes (CAS # 1330-20-7) is 390 μg/m3 with annual averaging time.

### Other adverse effects

# **SECTION 13: Disposal considerations**

#### Waste treatment methods

#### **Product**

See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

## Incompatibilities

Vapor may form explosive mixture with air. Incompatible with oxidizers (chlorates, nitrates, peroxides, permanganates, perchlorates, chlorine, bromine, fluorine, etc.); contact may cause fires or explosions. Keep away from alkaline materials, strong bases, strong acids, oxoacids, and epoxides. Electrostatic charges can be generated from agitation or flow.

## **Waste Disposal**

Consult with environmental regulatory agencies for guidance on acceptable disposal practices. Generators of waste containing this contaminant (≥100 kg/mo) must conform with EPA regulations governing storage, transportation, treatment, and waste disposal. Incineration.

# **SECTION 14: Transport information**

#### **UN** number

ADR/RID: 1307 IMDG: 1307

## **UN proper shipping name**

ADR/RID: XYLENES IMDG: XYLENES IATA: Xylenes

## Transport hazard class(es)

ADR/RID: 3 IMDG: 3 IATA: 3

## **Packaging group**

ADR/RID: III IMDG: III IATA: III

## **Environmental hazards**

ADR/RID: no IMDG Marine pollutant: no IATA: no

## Special precautions for user

No data available

# **SECTION 15: Regulatory information**

Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Regulations on the Safety Management of Hazardous Chemicals

China Catalog of Hazardous chemicals 2015:Listed. website: https://www.mem.gov.cn/

#### Measures for Environmental Management of New Chemical Substances

Chinese Chemical Inventory of Existing Chemical Substances (China IECSC):Listed. website: https://www.mee.gov.cn/

European Inventory of Existing Commercial Chemical Substances (EINECS):Listed. website: https://echa.europa.eu/

Vietnam National Chemical Inventory:Listed. website: https://chemicaldata.gov.vn/

Korea Existing Chemicals List (KECL):Listed. website: http://ncis.nier.go.kr

United States Toxic Substances Control Act (TSCA) Inventory:Listed. website: https://www.epa.gov/

Philippines Inventory of Chemicals and Chemical Substances (PICCS):Listed. website: https://emb.gov.ph/

New Zealand Inventory of Chemicals (NZIoC):Listed. website: https://www.epa.govt.nz/

EC Inventory:Listed.

## SECTION 16: Other information

## Abbreviations and acronyms

CAS: Chemical Abstracts Service

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

RID: Regulation concerning the International Carriage of Dangerous Goods by Rail

IMDG: International Maritime Dangerous Goods

IATA: International Air Transportation Association

TWA: Time Weighted Average

STEL: Short term exposure limit

LC50: Lethal Concentration 50%

LD50: Lethal Dose 50%

EC50: Effective Concentration 50%

#### References

- [1] CAMEO Chemicals, website: http://cameochemicals.noaa.gov/search/simple
- [2] ChemlDplus, website: http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp
- [3] ECHA European Chemicals Agency, website: https://echa.europa.eu/
- [4] eChemPortal The Global Portal to Information on Chemical Substances by OECD, website:

http://www.echemportal.org/echemportal/index?pageID=0&request\_locale=en

- [5] ERG Emergency Response Guidebook by U.S. Department of Transportation, website: http://www.phmsa.dot.gov/hazmat/library/erg
- [6] Germany GESTIS-database on hazard substance, website: http://www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index-2.jsp
- [7] HSDB Hazardous Substances Data Bank, website: https://toxnet.nlm.nih.gov/newtoxnet/hsdb.htm
- [8] IARC International Agency for Research on Cancer, website: http://www.iarc.fr/
- [9] IPCS The International Chemical Safety Cards (ICSC), website: http://www.ilo.org/dyn/icsc/showcard.home
- 【10】 Sigma-Aldrich, website: https://www.sigmaaldrich.com/

## Other Information

Depending on the degree of exposure, periodic medical examination is indicated. The recommendations on this Card also apply to technical xylene. See ICSCs 0084 and 0086.

#### Disclaimer:

The information in this MSDS is only applicable to the specified product, unless otherwise specified, it is not applicable to the mixture of this product and other substances. This MSDS only provides information on the safety of the product for those who have received the appropriate professional training for the user of the product. Users of this MSDS must make independent judgments on the applicability of this SDS. The authors of this MSDS will not be held responsible for any harm caused by the use of this MSDS.